

PLANAFLEX H05VVH2-F



Description

PLANAFLEX H05VVH2-F cables are indicated for indoor mobile installations and household appliances with medium mechanical strain, their main use being for domestic applications.

Reference Standards UNE-EN 50525-2-11, EN 50525-2-11

Applications

- Suitable for the following installations:
- Indoor or receiver installations
 - Installations in premises with special characteristics
 - Receiver installations
 - Electrical installations in furnishings

Technical Characteristics

1. Conductor	Flexible electrolytic copper conductor (Class V) according to BS EN 60228:2005 (previously BS6360) and UNE 60228
2. Insulation	PVC insulation, type TI-2, according to BS7655 and HD 21.5S3:1994/A2:2001
3. Sheath	PVC sheath, Type TM-2, according to BS 7655, UNE-EN 50363-4-1 and EN 50363-4-1
Nominal voltage	300/500V
Test voltage	2.000 V A.C.
Maximum temperature	70 °C
Colours	According to UNE 21089 and HD 308 S2 (colour-marked for less than five drivers), UNE-EN 50334 and EN 50334 (marked by registration for more than five drivers)
No flame spread	According to UNE-EN 60332-1-2, EN 60332-1-2 and IEC 60332-1-2

Dimensions

Section (mm ²)	Resistance at 20°C (Ohm/km)	External Diameter (mm)	Weight (kg/km)	Class
2x1	19,5	5,3	50	Eca
2x1,5	13,3	5,8	62	Eca

The information contained on this page is for information only and does not constitute a contractual commitment of any kind from Cables RCT. 17 de julio de 2024
Cables RCT, as a consequence of his continuous improvement process, may modify any technical specification without further notice.

