

Cables 300/500 V

H05V-U



Description

These cables are indicated for executing permanent protected installations, electrical control panels and signal or control circuits.

Reference Standards: UNE-EN 50525-2-31, EN 50525-2-31 and IEC 60227-3

Applications

Suitable for the following installations:

- Outdoor lighting installations. Earthing
- Indoor or receiver installations
- Indoor installations in housing
- Indoor installations in housing. Premises that contain a bath or shower
- Installations in premises with special characteristics
- Electrical installations in caravans and in caravans parks

Technical Characteristics

1. Conductor	Rigid electrolytic copper conductor (Class I) according to BS EN 60228:2005 (previously BS6360) and EN 60228.
2. Insulation	PVC insulation type TI-1 according to BS7655 and HD 21.3S3:1995/A2:2008.
Nominal voltage	300/500 V
Test voltage	2.000 V A.C.
Maximum temperature	70 °C

Other characteristics

Colours according to HD 21.1S4:2002

Non-flame propagating according to UNE-EN 60332-1-2, EN 60332-1-2 and IEC 60332-1-2

PVC insulation with reduced hydrogen chloride (HCL) emission

CPR Classification according to EN 50575

Dimensions

Section (mm ²)	Resistance at 20 °C (Ohm/km)	External Diameter (mm)	Weight (kg/km)	Class
1x0,5	36	2,00	8	Eca
1x0,75	24,5	2,20	11	Eca
1x1	18,1	2,30	13	Eca

The information contained on this page is for information only and does not constitute a contractual commitment of any kind from Cables RCT. Cables RCT, as a consequence of his continuous improvement process, may modify any technical specification without further notice.



HEADQUARTER ZARAGOZA
T. 976 500 120
info@rct.es

DELEGATION BARCELONA
T. 93 307 95 62
barna@rct.es

DELEGATION MADRID
T. 91 691 85 48
madrid@rct.es

DELEGATION SEVILLA
T. 954 354 946
sevilla@rct.es

DELEGATION VALENCIA
T. 96 375 90 70
valencia@rct.es

cablesrct.com