

Cables 300/500 V

H05Z-U



Description

These cables are suitable for setting up cable installations for panels, especially when we require low corrosive gas and fume emission and an improved behaviour with temperature.

Reference Standards: UNE-EN 50525-3-41, EN 50525-3-41, IEC 60227-3

Applications

Indicated for the following installations:

- Wiring of panels
- Premises with public attendance

Technical Characteristics

1. Conductor	Electrolytic copper Class I in accordance with UNE-EN 60228 and EN 60228
2. Insulation	Thermosetting material with polyolefin base with low fume and corrosive gas emission, type EI-5, in accordance with UNE 21027-9 and HD 22.9S3:2007
Nominal voltage	300/500 V
Test voltage	2.000 V A.C.
Maximum temperature	90 °C
Other characteristics	
Colours in accordance with UNE 21027 and HD 22.1S4	
Non-flame propagating according to UNE-EN 60332-1-2, EN 60332-1-2 and IEC 60332-1-2	
Low halogen content in accordance with UNE 21027-9, HD 22.9S3:2007 and IEC 60754-1 and 60754-2-2	
Low corrosive gas emission in accordance with UNE 21027-9, HD 22.9S3:2007 and IEC 60754-1 and 60754-2-2	
Low opaque gas emission in accordance with UNE-EN 61034, EN 61034 and IEC 61034	
Curvature radius: 4 x external diameter	

Dimensions

Section (mm ²)	Resistance at 20 °C (Ohm/km)	External Diameter (mm)	Weight (kg/km)
1x0,5	36	2,00	8
1x0,75	24,5	2,20	11
1x1	18,1	2,30	13



HEADQUARTER ZARAGOZA
T. 976 500 120
info@rct.es

DELEGATION BARCELONA
T. 93 307 95 62
barna@rct.es

DELEGATION MADRID
T. 91 691 85 48
madrid@rct.es

DELEGATION SEVILLA
T. 954 354 946
sevilla@rct.es

DELEGATION VALENCIA
T. 96 375 90 70
valencia@rct.es

cablesrct.com