

Cables 450/750 V

H07V-U



Description

These cables are indicated for executing permanent installations in housing, premises and offices, electrical control panels, as well as domestic and industrial lighting. They are easy to install thanks to their superslide insulation.

Reference Standards: UNE-EN 50525-2-31, EN 50525-2-31 and IEC 60227-3

Applications

suitable for following installations:

- Outdoor lighting installations
- Earthing/Indoor or receiver installations
- Indoor installations in housing
- Premises that contain a bath or shower
- Installations in premises with fire or explosion risk
- Installations in premises with special characteristics
- Electrical installations in caravans and in caravans parks

Technical Characteristics

1. Conductor	Electrolytic copper conductor, Class I, according to BS EN 60228:2005 (previously BS6360) and EN 60228.
2. Insulation	PVC insulation, type TI-1, according to BS 7655 and HD 21.3S3:1995/A2:2008.
Nominal voltage	450/750 V
Test voltage	2.500 V A.C.
Maximum temperature	70 °C
Other characteristics	

Colours according to UNE-EN 50525-1 and EN 50525-1

Non-flame propagating according to UNE-EN 60332-1-2, EN 60332-1-2 and IEC 60332-1-2

CPR Classification according to EN 50575

Dimensions

Section (mm ²)	Resistance at 20 °C (Ohm/km)	External Diameter (mm)	Weight (kg/km)	Class
1x1,5	12,1	2,75	19	Eca
1x2,5	7,41	3,40	31	Eca
1x4	4,61	3,60	45	Eca
1x6	3,08	4,30	66	Eca
1x10	1,83	5,30	105	Eca

The information contained on this page is for information only and does not constitute a contractual commitment of any kind from Cables RCT. 3 July 2018
Cables RCT, as a consequence of his continuous improvement process, may modify any technical specification without further notice.



HEADQUARTER ZARAGOZA
T. 976 500 120
info@rct.es

DELEGATION BARCELONA
T. 93 307 95 62
barna@rct.es

DELEGATION MADRID
T. 91 691 85 48
madrid@rct.es

DELEGATION SEVILLA
T. 954 354 946
sevilla@rct.es

DELEGATION VALENCIA
T. 96 375 90 70
valencia@rct.es

cablesrct.com