

Cables 300/300 V

Style 1569



Description

Cables Style 1007 / 1569 are intended for electric and electronic appliances internal wiring where a special performance against high temperatures is required.

Reference Standards: UL 758

Applications

Electric and electronic appliances internal wiring.

Technical Characteristics

1 Conductor	Stranded electrolytic copper (tinned) (Class V) according to UL 758
2 Insulation	PVC according to UL 758 and CSA 2.2
Nominal voltage	300/300
Test voltage	2.000 V AC
Maximum temperature	-30°C / 105 °C

Other characteristics

Non flame-propagating according to UL 758
Also available in polished copper

Dimensions

AWG	Resistance at 20 °C (Ohm/km)	External Diameter (mm)	Weight (kg/km)
22	59,4	1,60	5
20	36,7	1,90	7
18	23,5	2,20	11
16	14,6	2,40	16

The information contained on this page is for information only and does not constitute a contractual commitment of any kind from Cables RCT. 25 June 2020
Cables RCT, as a consequence of his continuous improvement process, may modify any technical specification without further notice.



HEADQUARTER ZARAGOZA
T. 976 500 120
info@rct.es

DELEGATION BARCELONA
T. 93 307 95 62
barna@rct.es

DELEGATION MADRID
T. 91 691 85 48
madrid@rct.es

DELEGATION SEVILLA
T. 954 354 946
sevilla@rct.es

DELEGATION VALENCIA
T. 96 375 90 70
valencia@rct.es

cablesrct.com