


Cables 450/750 V

TRIPLÍN™ H07V-U



Description

These cables are indicated for executing permanent installations in housing, premises and offices, electrical control panels, as well as domestic and industrial lighting. The use of this product range facilitates the installation, reducing execution times and costs. This product is manufactured according to the utility model (patent) no. 200702014, property of Cables RCT. Reference Standards: UNE-EN 50525-2-31, EN 50525-2-31 and IEC 60227-3

Applications

Suitable for the following installations:

- Outdoor lighting installations
- Earthing/Indoor or receiver installations
- Indoor installations in housing
- Premises that contain a bath or shower
- Installations in premises with fire or explosion risk
- Installations in premises with special characteristics
- Electrical installations in caravans and in caravans parks

Technical Characteristics

1. Conductor	Electrolytic copper conductor (Class I) according to BS EN 60228:2005 (previously BS6360) and EN 60228.
2. Insulation	PVC insulation, type TI-1, according to UNE 21031-3 and HD21.S2:1995/A2:2008.
Nominal voltage	450/750 V
Test voltage	2.500 V A.C.
Maximum temperature	70 °C

Other characteristics

Colours according to UNE-EN 50525-1 and EN 50525-1

Non-flame propagating according to UNE-EN 60332-1-2, EN 60332-1-2 and IEC 60332-1-2

Dimensions

Section (mm ²)	Resistance at 20 °C (Ohm/km)	External Diameter (mm)	Weight (kg/km)	Class
1x1,5	12,1	2,70	19	Eca
1x2,5	7,41	3,30	30	Eca
1x4	4,61	4,10	45	Eca
1x6	3,08	4,30	66	Eca
1x10	1,83	5,60	105	Eca



HEADQUARTER ZARAGOZA
T. 976 500 120
info@rct.es

DELEGATION BARCELONA
T. 93 307 95 62
barna@rct.es

DELEGATION MADRID
T. 91 691 85 48
madrid@rct.es

DELEGATION SEVILLA
T. 954 354 946
sevilla@rct.es

DELEGATION VALENCIA
T. 96 375 90 70
valencia@rct.es

cablesrct.com