

Cables 300/500 V

Tri-Rated UL-CSA H05V2-K



Description

Used for internal wiring of control equipment, in those places where special high temperature behaviour is required. Its standardisation, HD 21, BS 6231, UL 758 and CSA 22.2, makes it adequate to be marketed all over the world without technical barriers.

Reference Standards: BS 6231, UL 758, CSA 22.2, UNE-EN 50525-2-31, EN 50525-2-31

Applications

Suitable for the following installations:

- Internal or external wiring for electrical or electronic equipment.
- Installations in premises with special characteristics: premises at high temperature

Technical Characteristics

1. Conductor	Flexible electrolytic copper conductor (class V) according to BS EN 60228:2005 (previously BS6360) and UNE 60228..
2. Insulation	PVC insulation type TI-3 according to BS 6231, UL 758, CSA 22.2, UNE 21031-7 and HD 21.7S2:1996/11:1999.
Nominal voltage	300/500V UL 600V BS 0,6/1kV
Test voltage	2.000 V A.C.
Maximum temperature	105 °C

Other characteristics

Colours according to UNE-EN 50525-1 and EN 50525-1

Non-flame propagating according to UNE-EN 60332-1-2, EN 60332-1-2 and IEC 60332-1-2

Insulation with reduced hydrogen chloride (HCl) emission

CPR Classification according to EN 50575

Dimensions

Section (mm ²)	AWG	Resistance at 20 °C (Ohm/km)	External Diameter (mm)	Weight (kg/km)	Style	Class
1x0,5	22	39	2,40	9	1015	Eca
1x0,75	20	26	2,60	12	1015	Eca
1x1	18	19,5	2,80	15	1015	Eca

The information contained on this page is for information only and does not constitute a contractual commitment of any kind from Cables RCT. 4 January 2019
Cables RCT, as a consequence of his continuous improvement process, may modify any technical specification without further notice.



HEADQUARTER ZARAGOZA
T. 976 500 120
info@rct.es

DELEGATION BARCELONA
T. 93 307 95 62
barna@rct.es

DELEGATION MADRID
T. 91 691 85 48
madrid@rct.es

DELEGATION SEVILLA
T. 954 354 946
sevilla@rct.es

DELEGATION VALENCIA
T. 96 375 90 70
valencia@rct.es

cablesrct.com